

## DECK EQUIPMENT – LIFEGUARD CHAIRS

### G. DECK EQUIPMENT

All deck equipment and the Pool Contractor shall furnish related accessories specified herein. Installation shall be by the Pool Contractor unless otherwise dictated by the project drawings. Paddock Pool Equipment Company, Inc., of Rock Hill, South Carolina, shall supply the deck equipment and related accessories. Substitutions may be considered if offered according to the conditions set forth in the appropriate section of these specifications. Products offered by a company not regularly engaged in the manufacture of such equipment shall not be acceptable for this project. The deck equipment shall be guaranteed for a period of one year against defects in workmanship or material.

#### G. 6 FT PORTABLE LIFEGUARD CHAIR, PADDOCK MODEL \_\_\_\_\_

The lifeguard chair shall be portable and shall have a molded fiberglass seat installed 6'-1½" above the deck. The frame of the chair shall be welded and shall be fabricated of 1.9 O.D. x .065" wall & .083" wall Type 304 stainless steel tubing with a 320 grit finish. Frames, which are bolted together, shall not be acceptable. The framework shall move across the deck on 2" x 4" diameter polyofin wheels installed on ¾" stainless steel axle assemblies. The platform rails shall be fabricated entirely of stainless steel and extruded PVC "I" beam sections. The surface of the extruded PVC sections shall be serrated to form a non-skid surface. The top surface sections shall be 5/8" wide and the space between extruded sections shall not exceed 1/8". A 15-degree sloping ladder shall reach the platform, which is 19" wide. The bottom of the ladder and back rails shall be fitted with white rubber bumpers, which shall bear on the deck. The ladder treads shall be stainless steel 19" long x 4" wide with a slip-resistant surface. The lifeguard chair shall be supplied with an umbrella socket fabricated of Type 304 stainless steel integral to the stainless steel framework on one side of the stand behind the seat.

#### G. 4½' PORTABLE LIFEGUARD STATION, PADDOCK MODEL \_\_\_\_\_

The portable lifeguard station frame shall be fabricated from Type 304 stainless steel with a molded fiberglass seat 4½ feet above the pool deck. The rigid 48" x 48" slip-resistant PVC "I" beam platform shall allow extra space for lifeguard changes and shall be reached via a rear-mounted integral ladder with two 19" stainless steel treads. Rubber bumpers protect the deck when the chair is in place. Wheels shall be secured to the frame to allow for easy position at various poolside locations. An umbrella socket on one side behind the seat shall be integral to the chair frame.

#### G. 2½' PORTABLE LIFEGUARD STATION, PADDOCK MODEL \_\_\_\_\_

The 2½' lifeguard chair shall provide maximum safety and excellent visibility in recreational or instruction settings. It shall be fabricated from Type 304 stainless steel with a molded fiberglass swivel seat 30 inches above the pool deck mounted on a 3" stainless steel pedestal. The 48" x 48" slip-resistant PVC "I" beam platform shall be one step from ground level and shall be accessed from the front or rear. Wheels secured to the frame allow for easy positioning at various locations in the zero-depth or shallow area. An umbrellas socket on one side behind the seat shall be integral to the chair frame.

#### G. LIFEGUARD OBSERVATION PLATFORM CHAIR, PADDOCK MODEL \_\_\_\_\_

The observation platform shall provide maximum visibility across a wide area and extra space for uninterrupted lifeguard station changes. Dimensions shall be 36" x 78" x 74" with a welded Type 304 stainless steel frame and molded fiberglass seat 5 feet above the pool deck. The rigid 60" wide slip-resistant PVC "I" beam platform allows room for more than one lifeguard and shall be reached via two side-mounted 15-degree sloping ladders, each with two 19" stainless steel treads. Curved handrails permit safe access and descent and provide security for lifeguards standing on the platform. A fixed cross brace shall be placed directly behind the seat for added protection. Rubber bumpers protect the deck when the chair is in place. Wheels shall be secured to the frame to allow for easy positioning at various poolside locations. An umbrella socket on one side behind the seat shall be integral to the chair frame.

#### G. LIFEGUARD CHAIR UMBRELLA

There shall be supplied one umbrella for each lifeguard chair specified. Alternation red and white panels open to 63 ½ "and retract for storage. The 1" steel pole has a swivel joint to tilt the umbrella when in use. Paddock Model 4708.

#### G. LIFE HOOK

The life hook with one-piece 16" aluminum handle shall be supplied, Paddock Model 4723.

#### G. RING BUOY

The 24" Ring Buoy with white canvas cover designed and manufactured to U.S. Coast Guard requirements shall be supplied, Paddock Model 4726.